# Safety Data Sheet

Copyright, 2016, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:

07-4015-9

Version number:

15.00

Revision date:

27/04/2016

Supersedes date:

14/10/2014

Transportation version number: 1.00 (31/03/2011)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

### Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone:

+44 (0)1344 858 000

E Mail:

tox.uk@mmm.com

Website:

www.3M.com/uk

# 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

## 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

## CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314 Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

### SIGNAL WORD

DANGER.

# 3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

Symbols:

GHS05 (Corrosion) | GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient 3,3'-Oxybis(ethyleneoxy)bis(propylamine) CAS Nbr 4246-51-9 % by Wt 60 - 100

HAZARD STATEMENTS:

H314 H317 Causes severe skin burns and eye damage. May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P260B P280D Do not breathe dust.

Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310

P333 + P313

Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314 H317 Causes severe skin burns and eye damage. May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P260B

Do not breathe dust.

P280D

Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 P333 + P313 Immediately call a POISON CENTRE or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Contains 2% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

May cause chemical gastrointestinal burns.

# SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	60 - 100	Skin Sens. 1, H317 (Vendor) Skin Corr. 1B, H314 (Self Classified)
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	7 - 13	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 (CLP)
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5		5 - 10	
Bis[(dimethylamino)methyl]phenol	71074-89-0	275-162-0	1 - 5	Acute Tox. 4, H302; Skin Corr. 1B, H314 (Self Classified)

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

## Eve contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

#### Condition

During combustion.

Carbon dioxide.

During combustion.

### 5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated,

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

#### 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Sweep up. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

# 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient

112945-52-5 UK HSC

CAS Nbr

Limit type

Additional comments

Silicon dioxide

Agency

TWA(as inhalable dust):6 mg/m3;TWA(as respirable

dust):2.4 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

## 8.2. Exposure controls

8.2.1. Engineering controls

Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material Fluoroelastomer Nitrile rubber. Thickness (mm)

No data available No data available

Breakthrough Time No data available

No data available exposure (eg. spraying, high splash potential etc.), then

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

#### Respiratory protection

Wear respiratory protection if ventilation is inadequate to prevent overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state Specific Physical Form:

Paste

Appearance/Odour

Red thick paste. Amine odour

Odour threshold

No data available. Not applicable.

Boiling point/boiling range

>=100 °C Not applicable.

Melting point Flammability (solid, gas) Explosive properties

Not classified Not classified

Oxidising properties

Flash point

Autoignition temperature Flammable Limits(LEL) Flammable Limits(UEL)

Vapour pressure

Relative density Water solubility

Solubility- non-water

Partition coefficient: n-octanol/water

**Evaporation rate** Vapour density

Decomposition temperature

Viscosity Density

Not classified

>=100 °C [Test Method:Closed Cup]

No data available. No data available. No data available.

No data available.

1.04 - 1.08 [Ref Std: WATER=1]

Negligible

No data available.

No data available. No data available.

No data available No data available.

10 - 25 Pa-s [@ 23 °C]

1.04 - 1.08 g/ml

9.2. Other information

Percent volatile

0 % weight

# SECTION 10: Stability and reactivity

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

# 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

Heat.

Sparks and/or flames.

#### 10.5 Incompatible materials

Strong oxidising agents.

## 10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

# SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 11.1 Information on Toxicological effects

# Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

#### Eve contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

### Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

# Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Name Name	Route	Species	Value
Overall product	Dermal	100	No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
3. F-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,500 mg/kg
3,3'-Oxybis(ethyleneoxy)his(propylamine)	Ingestion	Rat	LD50 3,160 mg/kg
2.4,6-Tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2.4,6-Tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
Synthetic amorphous silica, furned, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion	2000	LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

# Shin Correction Arritation

Name	Species	Value	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive	
2,4,6-Tris(dimethylaminomethyl)phenol	Rabbit	Corrosive	
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation	
Bis[(dimethylamino)methyl]phenol	similar compoun ds	Corrosive	

Serious Eye Damage/Irritation

Name	Species	Value	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	similar health hazards	Corrosive	
2,4,6-Tris(dimethylaminomethyl)phenol	Rabbit	Corrosive	

Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation	
Bis[(dimethylamino)methyl]phenol	similar compoun ds	Corrosive	

#### Skin Sensitisation

Name	Species	Value
2,4,6-Tris(dimethylaminomethyl)phenol	Guinea	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	Human and animal	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Name	Route	Value	
2.4.6-Tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic	
Synthetic amorphous silica, famed, crystalline-free	In Vitro	Not mutagenic	

Name	Route	Species	Value
Synthetic amorphous silica, fumed, crystalline-free	Not specified.	533555555	Some positive data exist, but the data are not sufficient for classification

# Reproductive Toxicity

Panyadustive and/or Developmental Effects

Name.	Route	Value	Species	Test result	Exposure Duration
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

# Target Organ(s)

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2,4,6- Tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - reneated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,4,6- Tris(dimethylaminomethyl lohenol	Dermal	skin   liver   nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 125 mg/kg/day	28 days
2,4,6- Tris(dimethylaminomethyl	Dermal	auditory system   hematopoietic system   eyes	All data are negative	Rat	NOAEL 125 mg/kg/day	28 days

Synthetic amorphous Inhalation respiratory system   All data are negative silicosis   All data are negative silicosis	Human	available	occupational exposure
---	-------	-----------	--------------------------

# Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

## 12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Dxybis(ethylen eoxy)bis(propy amine)	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	220 mg/l
3,3'- Oxybis(ethylen eoxy)bis(propy lamine)	4246-51-9	Algae	Experimental	72 hours	EC50	69 mg/l
3,3'- Oxybis(ethylen eoxy)bis(propy lamine)	4246-51-9	Crustacea	Experimental	48 hours	EC50	220 mg/l
2,4,6- Tris(dimethyla minomethyl)ph enol	90-72-2	Grass Shrimp	Laboratory	96 hours	LC50	718 mg/l
2,4,6- Tris(dimethyla minomethyl)ph enol	90-72-2	Common Carp	Laboratory	96 hours	LC50	175 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Zebra Fish	Analogous Compound	96 hours	LC50	5,000 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Green algae	Analogous Compound	72 hours	EC50	440 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Water flea	Analogous Compound	48 hours	EC50	7,600 mg/l
Bis[(dimethyla			Data not	1		

mino)methyl]p henol	available or insufficient for classification
	elassification

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2,4,6- Tris(dimethyla minomethyl)ph enol	90-72-2	Calculated Photolysis		Photolytic half- life (in air)	1/2)	Other methods
Bis[(dimethyla mino)methyl]p henol	71074-89-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6- Tris(dimethyla minomethyl)ph enol	90-72-2	Laboratory Biodegradation	28 days	BOD	4 % weight	OECD 301D - Closed bottle test
3,3'- Oxybis(ethylen eoxy)bis(propy lamine)	4246-51-9	Estimated Biodegradation	28 days	BOD	12.6 % weight	OECD 301C - MITI test (I)

# 12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Bis[(dimethyla mino)methyl]p henol	71074-89-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3,3'- Oxybis(ethylen eoxy)bis(propy lamine)	4246-51-9	Estimated Bioconcentrati on		Log Kow	-1.46	Other methods
2,4,6- Tris(dimethyla minomethyl)ph enol	90-72-2	Laboratory Bioconcentrati on		Log Kow	-0.66	Other methods

# 12.4. Mobility in soil

Please contact manufacturer for more details

# 12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

#### 12.6. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of completely cured (or polymerised) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# SECTION 14: Transportation information

ADR: UN3259; Amines, Solid, Corrosive, N.O.S. (3,3'-oxybis(ethyleneoxy)bis(propylamine)); 8; II; (E); C8.

IATA: UN3259; Amines, Solid, Corrosive, N.O.S. (3,3'-oxybis(ethyleneoxy)bis(propylamine)); 8; II.

IMDG: UN3259; Amines, Solid, Corrosive, N.O.S. (3,3'-oxybis(ethyleneoxy)bis(propylamine)); 8; II; FA, SB.

# SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information.

#### 15.2. Chemical Safety Assessment

Not applicable

H319

## SECTION 16: Other information

#### List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Causes serious eye irritation.

#### Revision information:

# 3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

Section 2: Indication of danger information information was deleted.

Label: Graphic Text information was deleted.

Label: Graphic information was deleted.

Label: Signal Word information was modified.

Section 2: Label ingredient information information was deleted.

Section 2: Label remarks information was deleted.

Section 2: R phrase reference information was deleted.

Risk phrase information was deleted.

Safety phrase information was deleted.

Section 3: Composition/Information of ingredients table information was modified.

Section 3: Reference to H statement explanation in Section 016 information was added.

Section 3: Reference to R and H statement explanation in Section 16 information was deleted.

Section 3: Reference to section 15 for Nota info information was deleted.

Section 5: Fire - Extinguishing media information information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Precautions safe handling information information was modified.

Section 8: Appropriate Engineering controls information information was modified.

Section 8: glove data value information was added.

Section 8: Skin protection - recommended gloves information information was deleted.

Section 9: Property description for optional properties information was added.

Section 9: Property description for optional properties information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Aspiration Hazard text information was added.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Health Effects - Ingestion information information was modified.

Section 11: Health Effects - Skin information information was modified.

Section 11: Reproductive and/or Developmental Effects text information was added.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Respiratory Sensitization text information was added.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 14: Transportation classification information was modified.

Section 16: List of relevant R phrase information information was deleted.

Section 16: List of relevant R-phrases information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk

Page: 12 of 12